



JINAN LIFT LIFTING MACHINERY CO.,LTD.

ADDRESS: NO.9,INDUSTRIAL PARK,JIBEI DEVELOPMENT ZONE, JINAN, SHANDONG, CHINA

WEBSITE: WWW.SCISSORLIFT.CN MOBILE: 0086-15866733173 TEL:0086-86345648

TECHNICAL SHEET

PRODUCT PICTURE FOR REFERENCE



BASIC TECHNICAL SPECIFICATIONS

Lift drive	hydraulic
Max. loading capacity	2000KG
Max.platform height	1700mm
Platform size	2000x2000mm
Overall size	2260x2650x2500mm

MAIN TECHNICAL SPECIFICATIONS

Main frame	high strength steel rectangular tube 120x60mm
Work platform main frame	high strength steel rectangular tube 80x40mm
Work platform surface	3mm thickness antiskid checkered plate
Guide rail group	C profile steel 120x70x20x5mm Q355B cold bending once forming
Lip plate	width 600mm
	surface 6mm thickness antiskid checkered steel plate

Tail-board	width 600mm
	surface 6mm thickness antiskid checkered steel plate and bottom with support beam reinforce
Control mode	24V safety voltage
Control device	control box
	remote controller
Industrial plug	Delixi brand
Hydraulic station	2.2KW 1Ph 220V 50HZ
Power voltage	1Ph 220V 50HZ
Guide rail group	2 sets
Lifting chain	high strength chain 16A and with manganese steel pull rod
Hydraulic cylinder	φ63mm x 2 sets
Tyre	2 universal wheels +2 directional wheels
	5 inches super heavy duty iron core polyurethane casters (double bearings and thickened bracket)
Leg for fixing	2 sets adjustable galvanized lead screws
Hydraulic pipe	high pressure double steel mesh rubber pipe Hebei Hengyu brand
Machine color	blue grey
Safety device	emergency descent device if power failure
	limit switch device

DESIGN DRAWING FOR YOUR REFERENCE



