JINAN LIFT LIFTING MACHINERY CO., LTD


ADDRESS: NO.9, INDUSTRIAL PARK, JIBEI DEVELOPMENT ZONE, JINAN, SHANDONG, CHINA WEBSITE: WWW.SCISSORLIFT.CN MOBILE: 0086-15866733173 TEL:0086-86345648


TECHNICAL SHEET


PRODUCT PICTURE FOR YOUR REFERENCE- BIGGEST MANUFACTURER SEELING



DESIGN DRAWING







TECHNICAL SPECIFICATIONS	
Lift drive	hydraulic
Max. working height	12000mm
Max. platform height	10000mm
Rated capacity	130KG
Platform size	650x650mm
Overall size (AxBxC)	1420x780x1970mm
Open size (WxL)	1702x1914mm
Min. ground clearance	0.05m
Wheel base	1290mm
Lifting speed	3-5m/min
Machine weight	about 420kg
Mast material	6.5mm thickness national standard aluminum profile
Hydraulic cylinder	1 set HSG40 Hebei "Hengyu" brand China famous
Hydraulic pipe	double-layer steel mesh high pressure oil pipe
Hydraulic station	China-Italy joint venture brand
Tire	Φ200mm polyurethane tyres
Motor power	1.1KW single phase 220V 50Hz
Control mode	electric rise and down
Electric switch box	1 set main control box
Remote controller	2 sets
Limit swith	Delixi or SREAW brand
Rust removal	shot blasting sandblasting derusting processing
Spraying treatment	electrostatic powder coating
FEATURES	
 Motor: CE certificate approved Hydraulic station: CE approved a. China-Italy joint venture, well pressure maintaining performance, zero leakage 	

b. emergency drop valve. When power cut off, the machine can go down by manual control.

c. spillover valve can prevent high pressure when the machine lifts up

>Hydraulic cylinder: wear-resisting and with imported seal ring, good sealability

>Oil tube: made of double-layer steel mesh, big compressive resistance

>Level measuring instrument can measure if the machine is in level condition

➢Rust removal :shot blasting, sandblasting treatment; remove rust on the surface of the steel structures and can make the surface of steel component generate a certain degree of uneven effect, which increase the adhesion of powder

Spraying treatment: electrostatic powder coating, to keep the coating appearance quality excellent, strong adhesion and mechanical strength, high brightness and no colr fades